

SOLUTION EASY ROOF SLIM SLATE COMPATIBILITY

IN ROOF MOUNTING SYSTEM
FOR PV MODULES

*EASY ROOF SLIM Solution according to
the new requirements of the «CEIAB Ardoise 2012».*



EASY ROOF SLIM ADVANTAGES



Modularity

«Mono frame» mounting system solution for Modular assembly
from 0,2kW to several MW

Each module can be individually replaced or removed

Lay out : portrait, pyramid assembly and miscellaneous forms

Easy to handle

Low weight (2,5 kg) & not bulky (1785 x 1061 mm) for an easy transport

Easy to install

Installation without any cut

Quick system for clamps and fixing flanges

Speed of mounting : 3kW with 2 fitters installed in 6 hours

Reliability

No seal

Advantageous design can answer to all kinds of roofs lay out even distorted with
a slope from 10° to 50°

Climate resistance approved for : UV ray, hail, rust, heat, snow and wind

(climate zones 1,2,3, 4 : snow & wind according to the regulation NV-65 & Eurocode)

Optimum operating performance : Every PV module's efficiency is optimized
thanks to fresh air entrance

Evacuation of rain water over the modules

Aesthetic

Black finition for side clamps and fixing flanges

Black finition for glazing bead (option)

Environment

EASY ROOF is 100 % recycable



EASY ROOF SYSTEM
BY IRFTS
SOLAR SOLUTIONS

Available : 1st Quater 2012